

Safety Data Sheet

CPVC-PVC PRIMER (PURPLE)

SDS Revision Date:

1/26/2023



1. Identification

1.1. Product identifier

Product Identity

CPVC-PVC PRIMER (Purple)

Alternate Names

20-625, Blended Formula, CPVC-PVC Primer, PVC & CPVC Primer with Dauber- 1/2 pt

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use

It is a low V.O.C, high primer that cuts gloss and softens surface prior to cementing.

Application Method

Read all precautions and instructions carefully before and after use.

1.3. Details of the supplier of the safety data sheet

Company Name

ComStar International Inc.
20-47 128th Street,
College Point, NY 11356

Telephone No.

718-445-7900
800-328-0142
Fax: 718-353-5998

Emergency 24 HR response No: 1-800-424-9300 & 703-527-3887 CHEMTREC

Note: The CHEMTREC phone number is only for emergencies involving spills, leaks, fire, exposure, or accident. Please direct all other inquiries to our customer service phone number.

2. Hazard(s) identification

GHS Classification:

2.1. Classification of the substance or mixture

Physical hazards	Flammable liquids	Category 2
Health hazards	Acute toxicity, Oral	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
Environmental hazards	Acute toxicity	None known
	Chronic toxicity	None known
Osha defined hazards	Not Classified	

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.

Safety Data Sheet

CPVC-PVC PRIMER (PURPLE)

SDS Revision Date:

1/26/2023



Signal Word:

Danger

[Hazard statement]

H225: Highly flammable liquid and vapor.

H319: Causes serious eye irritation

H332: Harmful if inhaled.

H335: May cause respiratory irritation. Harmful if swallowed and enters airways.

H336: May cause drowsiness or dizziness

[Precautionary statements]

[Prevention]:

P210: Keep away from heat/sparks/open flames/ hot surfaces- No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink, or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

P261: Avoid breathing dust/fumes/gas/mist/vapors/spray

P280: Wear protective gloves/protective clothing/eye protection/face protection

P304+P340: If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P403+P233: Store in a well-ventilated place. Keep container tightly closed

P501: Dispose of contents/containers in accordance with local regulation

[Response]:

If swallowed: Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Rinse mouth. Do not induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.

[Storage]:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

[Disposal]:

Dispose of contents/container in accordance with local/regional/national/international regulations.

Safety Data Sheet

CPVC-PVC PRIMER (PURPLE)

SDS Revision Date:

1/26/2023



3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Chemical name	Cas number	Weight %
ACETONE	67-64-1	25-40
CYCLOHEXANONE	108-94-1	25-40
TETRAHYDROFURAN	109-99-9	15-30
METHYL ETHYL KETONE	78-93-3	15-30

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is stopped, give artificial respiration. If breathing is difficult, give oxygen. Call a poison center or doctor/physician if you feel unwell.
Eyes	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin	Take off immediately all contaminated clothing. Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention.
Ingestion	Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content does not get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.
Likely Routes for Exposure	Inhalation, Eye and Skin Contact
Most important symptoms/effects, acute and delayed	Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness, and nausea. Skin irritation. May cause redness and pain.

Safety Data Sheet

CPVC-PVC PRIMER (PURPLE)

SDS Revision Date:

1/26/2023



Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Firefighting equipment/instructions	Firefighting equipment/instructions
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor. This product contains tetrahydrofuran that may form explosive organic peroxide when exposed to air or light or with age.

6. Accidental release measures

6.1. Personal precautions, protective equipment, and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Safety Data Sheet

CPVC-PVC PRIMER (PURPLE)

SDS Revision Date:

1/26/2023



Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand, or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements, or confined areas. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

7. Handling and storage

7.1. Precautions for safe handling

Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink, or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks, and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls and personal protection

8.1. Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

	Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m ³	1000 ppm
Cyclohexanone (CAS 108-94-1)	PEL	200 mg/m ³	50 ppm
Furan, Tetrahydro- (CAS 109-99-9)	PEL	590 mg/m ³	200 ppm

Safety Data Sheet

CPVC-PVC PRIMER (PURPLE)

SDS Revision Date:

1/26/2023



Methyl ethyl ketone (CAS 78-93-3)	PEL	590 mg/m ³
		200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
Cyclohexanone (CAS 108-94-1)	STEL	50 ppm
	TWA	20 ppm
Furan, Tetrahydro- (CAS 109-99-9)	STEL	735 mg/m ³
	TWA	250 ppm
Methyl ethyl ketone (CAS 78-93-3)	STEL	590 mg/m ³
	TWA	200 ppm
		885 mg/m ³
		300 ppm
	TWA	590 mg/m ³
		200 ppm

Biological limit values ACGIH Biological Exposure Indices
--

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
Cyclohexanone (CAS 108-94-1)	80 mg/l	1,2-Cyclohexanediol, with hydrolysis	Urine	*
Furan, Tetrahydro- (CAS 109-99-9)	2 mg/l	Tetrahydrofuran	Urine	*
Methyl ethyl ketone (CAS 78-93-3)	2 mg/l	MEK	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Cyclohexanone (CAS 108-94-1) US - Minnesota Haz Subs: Skin designation applies	Can be absorbed through the skin.
Cyclohexanone (CAS 108-94-1) US - Tennessee OELs: Skin designation	Skin designation applies.

Safety Data Sheet

CPVC-PVC PRIMER (PURPLE)

SDS Revision Date:

1/26/2023



Cyclohexanone (CAS 108-94-1) US ACGIH Threshold Limit Values: Skin designation	Can be absorbed through the skin.
Furan, Tetrahydro- (CAS 109-99-9) US. NIOSH: Pocket Guide to Chemical Hazards	Can be absorbed through the skin.
	Can be absorbed through the skin.

Engineering Controls: Use local exhaust as needed.

Monitoring: Maintain breathing zone airborne concentrations below exposure limits.

8.2. Personal Protective Equipment (PPE):

Eye Protection:

Avoid contact with eyes, wear splash-proof chemical goggles, face shield, safety glasses (spectacles) with brow guards and side shields, etc. as may be appropriate for the exposure.

Skin Protection:

Prevent contact with the skin as much as possible. Butyl rubber gloves should be used for frequent immersion. Use of solvent-resistant gloves or solvent-resistant barrier cream should provide adequate protection when normal adhesive application practices and procedures are used for making structural bonds.

Respiratory Protection:

Prevent inhalation of the solvents. Use in a well-ventilated room. Open doors and/or windows to ensure airflow and air changes. Use local exhaust ventilation to remove airborne contaminants from employee breathing zone and to keep contaminants below levels listed above. With normal use, the Exposure Limit Value will not usually be reached. When limits approached, use respiratory protection equipment.

9. Physical and chemical properties

Appearance	
Physical state	Liquid
Form	Translucent liquid
Color	Purple
Odor	Solvent
Odor threshold	Not available.
pH	Not available.
Melting point / freezing point	Not available.
Initial boiling point and boiling range	151 °F (66.11 °C)
Flash Point	14.0 - 23.0 °F (-10.0 - -5.0 °C)
Evaporation rate (Ether = 1)	5.5 - 8
Flammability (solid, gas)	Not available.

Safety Data Sheet

CPVC-PVC PRIMER (PURPLE)

SDS Revision Date:

1/26/2023



Upper/lower flammability or explosive limits

Flammability limit – lower (%)	1.8
Flammability limit – upper (%)	11.8
Explosive limit-lower (%)	Not available
Explosive limit-upper(%)	Not available
Vapor pressure	145 mm Hg @ 20 C
Vapor Density	2.5
Relative density Solubility(ies)	0.84 +/- 0.02 @20°C
Specific Gravity	0.934 @23°C (73°F)
Solubility in Water	Negligible
Partition coefficient n-octanol/water (Log Kow)	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Other information	
Bulk density	7 lb/gal
VOC (Weight %)	505 g/l SQACMD Method 24

10. Stability and reactivity

10.1. Conditions to avoid

Avoid heat, sparks, open flames, and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

10.2. Incompatible material

Acids. Strong oxidizing agents. Ammonia. Amines. Isocyanates. Caustics.

10.3. Reactivity

The product is stable and non-reactive under normal conditions of use, storage, and transport

10.4. Chemical stability

Material is stable under normal conditions.

10.5. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.6. Hazardous decomposition products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Safety Data Sheet

CPVC-PVC PRIMER (PURPLE)

SDS Revision Date:

1/26/2023



Inhalation	May be fatal if swallowed and enters airways. Headache. Nausea, vomiting. May cause irritation to the respiratory system. Vapors have a narcotic effect and may cause headache, fatigue, dizziness, and nausea. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	May be fatal if swallowed and enters airways. Harmful if swallowed. Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms related to the physical, chemical, and toxicological characteristics	Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness, nausea, and vomiting.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects. May cause respiratory irritation.

Components	Species	Test Results
------------	---------	--------------

Acetone (CAS 67-64-1)

Acute

Dermal

LD50	Rabbit	20 ml/kg
------	--------	----------

Inhalation

LC50	Rat	50 mg/l, 8 Hours
------	-----	------------------

Oral

LD50	Rat	5800 mg/kg
------	-----	------------

Cyclohexanone (CAS 108-94-1)

Acute

Dermal

LD50	Rabbit	948 mg/kg
------	--------	-----------

Inhalation

LC50	Rat	8000 ppm, 4 hours
------	-----	-------------------

Oral

LD50	Rat	1540 mg/kg
------	-----	------------

* Estimates for product may be based on additional component data not shown.

Safety Data Sheet

CPVC-PVC PRIMER (PURPLE)

SDS Revision Date:

1/26/2023



Skin corrosion/irritation
Serious eye damage/eye irritation

Causes skin irritation.
Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity In 2012 USEPA Integrated Risk Information System (IRIS) reviewed a two species inhalation lifetime study on THF conducted by NTP (1998). Male rats developed renal tumors and female mice developed liver tumors while neither the female rats nor the male mice showed similar results. Because the carcinogenic mechanisms could not be identified clearly in either species for either tumor, the EPA determined that the male rat and female mouse findings are relevant to the assessment of carcinogenic potential in humans. Therefore, the IRIS review concludes that these data in aggregate indicate that there is "suggestive evidence of carcinogenic potential" following exposure to THF by all routes of exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Cyclohexanone (CAS 108-94-1) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -Narcotic effects. May cause drowsiness and dizziness.
Respiratory tract irritation. single exposure

Specific target organ toxicity -Not classified. repeated exposure

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Safety Data Sheet

CPVC-PVC PRIMER (PURPLE)

SDS Revision Date:

1/26/2023



Components	Species	Test Results
Acetone (CAS 67-64-1) Aquatic		
Fish LC50 Cyclohexanone (CAS 108-94-1) Aquatic	Fathead minnow (Pimephales promelas) > 100 mg/l, 96 hrs	
Fish	Fathead minnow (Pimephales promelas) 481 - 578 mg/l, 96 hours	

*Estimates for product may be based on additional component data not shown.

Persistence and degradability	No data available on the degradability of this product
Bioaccumulative potential	No data available
Partition coefficient n-octanol/water (log kow)	
Acetone (CAS 67-64-1)	-0.24
Cyclohexanone (CAS 108-94)-1	0.81
Furan, Tetrahydro (CAS 109-99-9)	0.46
Methyl ethyl ketone (CAS 78-93-3)	0.29
Mobility in oil	No data available

Other adverse effects: No other adverse environmental effects (e.g. ozone, depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposable considerations	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, water ways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer, and the waste disposal company.
Waste from residues/unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

Safety Data Sheet

CPVC-PVC PRIMER (PURPLE)

SDS Revision Date:

1/26/2023



Waste treatment methods	Observe all federal, state, and local regulations when disposing of this substance
-------------------------	--

Follow local and national regulations. Consult disposal expert.

14. Transport information

	DOT (Domestic Surface Transportation)	IMO/IMDG (Ocean Transportation)	ICAO/IATA
14.1 UN number	UN1993	UN1993	UN1993
14.2. UN proper shipping name	Flammable liquids, n.o.s. (Methyl ethyl ketone RQ=26274 LBS, Acetone RQ=13130 LBS)	Flammable liquids, n.o.s. (Methyl ethyl ketone, Acetone)	Flammable liquids, n.o.s. (Methyl ethyl ketone, Acetone)
14.3. Transport hazard Class(es)	3	3	3
Subsidiary risk	-		
Label(s)	3		
14.4. Packing group	II	II	II
14.5. Environmental hazards		No	No
14.6. Special precautions for user	Read safety instructions, SDs & emergency procedures before handling.	Read safety instructions, SDs & emergency procedures before handling.	Read safety instructions, SDs & emergency procedures before handling.
ERG Code			3H
Special provisions	IB2, T7 TP1, TP8, TP28		
Packaging exceptions	150		
Packaging non bulk	202		
Packaging bulk	242		
Marine pollutant		No	
EMS		F-E, S-E	

Transport in bulk according to Annex II of Marpol 73/78 and the IBC Code -Not Available

15. Regulatory Information

US federal regulations: This product is "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910. 1200

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt D): Not Regulated.

OSHA Specifically Regulated Substances (29 CFR 1910. 1001-1050): Not Listed.

CERLA Hazardous Substances List (40 CFR 302.4)

Safety Data Sheet

CPVC-PVC PRIMER (PURPLE)

SDS Revision Date:

1/26/2023



Acetone (CAS 67-64-1)	LISTED
Cyclohexanone (CAS 108-94-1)	LISTED
Furan, Tetrahydro (CAS 109-99-9)	LISTED
Methyl ethyl ketone (CAS 78-93-3)	LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
 Immediate Hazard- Yes
 Delayed Hazard- No
 Fire Hazard- Yes
 Pressure Hazard- No
 Reactivity Hazard- No

SARA 302 Extremely hazardous substances: Not listed

SARA 311/312 Hazardous chemical: No

SARA 313 (TRI reporting): Not regulated

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List: Not regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention

(40 CFR 68.130) Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Methyl ethyl ketone (CAS 78-93-3) 6714

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

Methyl ethyl ketone (CAS 78-93-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

Methyl ethyl ketone (CAS 78-93-3) 6714

US state regulations

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)
 Cyclohexanone (CAS 108-94-1)
 Furan, Tetrahydro- (CAS 109-99-9)
 Methyl ethyl ketone (CAS 78-93-3)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)
 Cyclohexanone (CAS 108-94-1)
 Furan, Tetrahydro- (CAS 109-99-9)
 Methyl ethyl ketone (CAS 78-93-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Safety Data Sheet

CPVC-PVC PRIMER (PURPLE)

SDS Revision Date:

1/26/2023



Acetone (CAS 67-64-1)
 Cyclohexanone (CAS 108-94-1)
 Furan, Tetrahydro- (CAS 109-99-9)
 Methyl ethyl ketone (CAS 78-93-3)

US. Rhode Island RTK

Acetone (CAS 67-64-1)
 Cyclohexanone (CAS 108-94-1)
 Furan, Tetrahydro- (CAS 109-99-9)
 Methyl ethyl ketone (CAS 78-93-3)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country.

16. OTHER INFORMATION

Issue date	2/28/2022
Revision date	-
Version #	01
HMIS® ratings	Health:2 Flammability:3 Physical hazard:0



NFPA ratings

This product is intended for use by skilled individuals at their own risk. The information contained herein is based on data considered accurate based on current state of knowledge and experience. However, no warranty is expressed or implied regarding the accuracy of this data or the results to

Safety Data Sheet
CPVC-PVC PRIMER (PURPLE)

SDS Revision Date:

1/26/2023



be obtained from the use thereof.

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The opinions expressed are those of qualified experts within ComStar International Inc. We believe that the information contained is current as of the date of the Material Safety Data Sheet. Since the use of this information and of these opinions and the conditions of the use of the product are not within the control of ComStar International Inc., it is the user's obligation to determine the conditions of safe use of the product.

End of Document