

# Safety Data Sheet

## PAINT REMOVER

SDS Revision Date: 01/06/2022



### 1. Identification

#### 1.1. Product identifier

**Product Identity**

PAINT REMOVER

**Alternate Names**

55-029, Blended Formula, Paint Remover, Heavy Duty  
Paint Stripper- 55 gallon

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Intended use**

It is used to remove oil, acrylic, & water-based paints  
fast.

**Application Method**

Read all precautions and instructions carefully before  
and after use.

#### 1.3. Details of the supplier of the safety data sheet

**Company Name**

ComStar International Inc.  
20-47 128th Street,  
College Point, NY 11356

**Telephone No.**

718-445-7900  
800-328-0142  
Fax: 718-353-5998

**Emergency 24 HR response No:** 1-800-424-9300 & 703-527-3887 CHEMTREC

Note: The CHEMTREC phone number is only for emergencies involving spills, leaks, fire, exposure or  
accident. Please direct all other inquiries to our customer service phone number.

### 2. Hazard(s) identification

Classification of the chemical  
Clear colorless liquid. Sweet odor.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom  
2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Hazard classification:

Flammable Liquid - Category 4  
Acute Toxicity, inhalation - Category 3 (mist)  
Acute toxicity, dermal - Category 3  
Acute toxicity, oral - Category 4  
Skin Irritation - Category 2  
Serious eye damage/eye irritation - Category 2A

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



# Safety Data Sheet

## PAINT REMOVER

SDS Revision Date: 01/06/2022



### Warning

#### Hazard statement(s)

Combustible liquid.  
Toxic if inhaled.  
Toxic in contact with skin.  
Harmful if swallowed.  
Causes serious eye irritation.  
Causes skin irritation.

#### Precautionary statement(s)

Avoid breathing mist or vapours.  
Wash thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/clothing and eye/face protection.  
**If on skin:** Wash with plenty of soap and water.  
Take off contaminated clothing and wash it before reuse.  
If skin irritation occurs, get medical advice/attention.  
**If in eyes:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice/attention.  
**If inhaled:** Remove person to fresh air and keep comfortable for breathing.  
Call a poison center or doctor/physician if you feel unwell.  
**If swallowed:** Call a poison center/doctor if you feel unwell.  
Rinse mouth.  
**In case of fire:** Use water fog, dry chemical, CO2 or 'alcohol' foam to extinguish.  
Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Precautionary statement(s)

#### Other hazards:

Other hazards which do not result in classification:  
Burning produces obnoxious and toxic fumes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be an aspiration hazard. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

### 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
BUTYL CELLOSOLVE, CAS#: 111-76-2	>20	Skin Irrit. 2 H315 Eye Irrit. 2A H319	
n-METHYL PYRROLID CAS#: 872-50-4	>20	Skin Irrit. 2 H315 Eye Irrit. 2A H319	

# Safety Data Sheet

## PAINT REMOVER

SDS Revision Date: 01/06/2022



WATER	>15	Not Classified	
SURFACTANT PACKAGE (proprietary)	>10	Not Classified	

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

\*The full texts of the phrases are shown in Section 16.

### 4. First aid measures

#### 4.1. Description of first aid measures

<b>General</b>	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
<b>Inhalation</b>	If inhaled: Remove person to fresh air and keep comfortable for breathing. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Call a poison center or doctor/physician if you feel unwell.
<b>Eyes</b>	For eye contact, flush with running water for at least 15 minutes. If eye irritation persists: get medical advice/attention.
<b>Skin</b>	If on skin: Wash with plenty of soap and water. If skin irritation occurs, get medical advice/attention. Take off contaminated clothing and wash before re-use.
<b>Ingestion</b>	Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention if symptoms persist.

#### 4.2. Most important symptoms and effects, both acute and delayed

Toxic in contact with skin. Toxic if inhaled. Causes skin irritation. Harmful if swallowed. Contact may cause redness, swelling and a painful sensation. Causes serious eye irritation. Symptoms may include tearing, redness and discomfort. May cause respiratory irritation. May cause coughing and breathing difficulties. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard - material may cause lung inflammation or damage if it enters lungs through vomiting or swallowing. Inhaling high concentrations may cause central nervous system depression, with effects ranging from dizziness and headache to unconsciousness. Chronic overexposure to 2-butoxyethanol may cause liver, kidney and blood damage, based on animal data.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically

### 5. Fire-fighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>); Dry chemical; Alcohol resistant foam; Water fog.

##### Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

#### 5.2. Special hazards arising from the substance or mixture

Combustible liquid and vapor. Vapour can travel considerable distance and flashback to a source of ignition. Vapours are heavier than air and collect in confined and low-lying areas. Vapour will form a flammable/explosive mixture with air between the upper and lower flammable limits. May form explosive peroxides.

**Flammability classification (OSHA 29 CFR 1910.106)**

# Safety Data Sheet

## PAINT REMOVER

SDS Revision Date: 01/06/2022



Flammable liquid- Category 4

### Hazardous combustion products

Carbon dioxide and carbon monoxide.

### Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Special fire-fighting procedures

Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Do not allow run-off from firefighting to enter drains or water courses. Dike for water control.

ERG Guide No. ---

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

All persons dealing with the clean-up should wear the appropriate chemically protective equipment. Keep people away from and upwind of spill/leak. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

### 6.2. Environmental precautions

Do not allow material to contaminate ground water system. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply

### 6.3. Methods and material for containment and cleaning up

Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools and equipment in the clean-up process. Absorb material with inert absorbent, and place into labelled containers for disposal. Contact the proper local authorities. Refer to Section 13 for disposal of contaminated material.

### 6.4. Special spill response procedures

Contact appropriate local and provincial environmental authorities for assistance and/or reporting requirements. US CERCLA Reportable quantity (RQ): None.

## 7. Handling and storage

### 7.1. Precautions for safe handling

Keep away from heat, open flames and hot surfaces. - No smoking. Use only non-sparking tools. Use explosion-proof electrical and ventilating equipment. Wear protective gloves/clothing and eye/face protection. Use only in well-ventilated areas. Avoid breathing mist or vapours. Avoid contact with skin, eyes and clothing. Keep container tightly closed. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in cool/well-ventilated place. Store locked up. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking. Keep container tightly closed. May form explosive peroxides.

### 7.3. Incompatible materials

Strong oxidizers (e.g. Chlorine, Peroxides, etc.).

### 7.3. Specific end use(s)

No data available.

# Safety Data Sheet

## PAINT REMOVER

SDS Revision Date: 01/06/2022



### 8. Exposure controls and personal protection

#### 8.1. Control parameters

##### Exposure

CAS No.	Ingredient	Source	Value
111-76-2	BUTYL CELLOSOLVE,	OSHA	50 ppm(skin)
		ACGIH	20 ppm
		NIOSH	TWA 5 ppm (24 mg/m <sup>3</sup> ) [skin]
		Supplier	No Established Limit
872-50-4	n-METHYL PYRROLID	OSHA	500 PPM
		ACGIH	500 PPM
		NIOSH	No Established Limit
		Supplier	No Established Limit
N/A	WATER	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
N/A	SURFACTANT PACKAGE (proprietary)	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

#### Carcinogen Data

CAS No.	Ingredient	Source	Value
111-76-2	BUTYL CELLOSOLVE,	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
872-50-4	n-METHYL PYRROLID	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
N/A	WATER	OSHA	Select Carcinogen: No

# Safety Data Sheet

## PAINT REMOVER

SDS Revision Date: 01/06/2022



N/A	SURFACTANT PACKAGE (proprietary)	NTP	Known: No; Suspected: No
		IARC	Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

### 8.2. Exposure controls

- Respiratory** If airborne concentrations are above the permissible exposure limit or are not known, use NIOSH-approved respirators. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02. Advice should be sought from respiratory protection specialists.
- Eyes** Wear eye/face protection. Wear as appropriate: Tightly fitting safety goggles Other protective equipment: Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.
- Skin** Wear protective gloves/clothing. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Engineering Controls** Use only in well-ventilated areas. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof equipment. In case of insufficient ventilation wear suitable respiratory equipment.
- Other Work Practices** Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice

See section 2 for further details. - [Prevention]:

## 9. Physical and chemical properties

<b>Appearance</b>	Clear Liquid
<b>Odor</b>	Ether like odor
<b>Odor threshold</b>	0.48 ppm
<b>pH</b>	Not Measured
<b>Melting point / freezing point</b>	-75°C (-103°F)
<b>Initial boiling point and boiling range</b>	171°C (339.8°F)
<b>Flash Point</b>	67°C (152.6°F)
Flashpoint (Method)	closed cup
<b>Evaporation rate (Ether = 1)</b>	0.1

# Safety Data Sheet

## PAINT REMOVER

SDS Revision Date: 01/06/2022



<b>Flammability (solid, gas)</b>	Not Applicable
<b>Upper/lower flammability or explosive limits</b>	<b>Lower Explosive Limit:</b> 135°C(275°F): NA <b>Upper Explosive Limit:</b> 199°C(390°F): NA
<b>Vapor pressure (Pa)</b>	1.17 hPa
<b>Vapor Density</b>	(Air = 1) 4
<b>Specific Gravity</b>	0.90
<b>Solubility in Water</b>	Soluble. (900 g/l)
Other solubility(ies)	Soluble in most organic solvents.
<b>Partition coefficient n-octanol/water (Log Kow)</b>	0.81
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	124.7°C (DSC)
<b>Viscosity (cSt)</b>	3.642 mm/2s @ 20°C
<b>Volatiles (% by weight)</b>	NA
<b>Octanol/Water Partition Coefficient</b>	NA
<b>9.2. Other physical/chemical comments</b>	
Ignition temperature: 230°C (446°F)	
Molecular Weight: 118.2 g/mol	

## 10. Stability and reactivity

### 10.1. Reactivity

Not normally reactive. May form explosive peroxides.

### 10.2. Chemical stability

Stable under normal circumstances.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur

### 10.4. Conditions to avoid

Avoid heat, open flames, sparks, static electricity and electrical equipment. Do not use in areas without adequate ventilation. Avoid contact with incompatible materials. Avoid prolonged exposure to air. Prolonged storage. Do not allow evaporation to dryness.

### 10.5. Incompatible materials

Strong Oxidizers (e.g. Chlorine, Peroxides, etc.).

### 10.6. Hazardous decomposition products

No hazardous decomposition data available.

## 11. Toxicological information

### Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
BUTYL CELLOSOLVE (111-76-2)	470 mg/kg	220 mg/kg	2.21 mg/L	No data available	No data available

# Safety Data Sheet

## PAINT REMOVER

SDS Revision Date: 01/06/2022



Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

### Information on likely routes of exposure:

Routes of entry inhalation: YES

Routes of entry skin & eye: YES

Routes of entry Ingestion: YES :

Routes of exposure skin absorption YES:

### Potential Health Effects:

Sign and symptoms Inhalation: Harmful if inhaled. May cause respiratory irritation. Symptoms may include coughing and sneezing. Inhalation may cause headache, nausea and central nervous effects such as dizziness, coordination difficulties and unconsciousness. Could result in pulmonary edema (fluid accumulation).

Sign and symptoms ingestion: Harmful if swallowed. Ingestion can cause gastrointestinal irritation, nausea, and diarrhea. May be an aspiration hazard.

Sign and symptoms skin : This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Skin irritation. Category 2 Causes skin irritation. Toxic in contact with skin. May be absorbed and cause symptoms similar to those for inhalation.

Sign and symptoms eyes: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Eye damage/irritation Category 2A Causes serious eye irritation. Repeated exposure may cause skin dryness or cracking. Chronic overexposure to 2-butoxyethanol may cause liver, kidney and blood damage, based on animal data.:

### Potential Chronic Health Effects

Mutagenicity: Not expected to be mutagenic in humans.

Carcinogenicity: No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP. Reproductive effects & Teratogenicity: This product is not expected to cause reproductive or developmental effects.

Sensitization to material: Not expected to be a skin or respiratory sensitizer.

Specific target organ effects: According to the classification criteria of U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015), this product is not expected to cause target organ toxicity through single or repeated exposures.

Medical conditions aggravated by overexposure: Pre-existing skin, eye, respiratory and central nervous system disorders.

Synergistic materials: No information available.

Toxicological data: See below for toxicological data on the substance.

Acute Toxicity, inhalation - Category 3 (vapor) A

cute toxicity, dermal - Category 3

Acute toxicity, oral - Category 4

### Toxicological data

See below for toxicological data on the substance.

# Safety Data Sheet

## PAINT REMOVER

SDS Revision Date: 01/06/2022



Chemical name	LC50(4hr) inh, rat	LD50 (Oral, rat)	LD50 (Rabbit, dermal)
BUTYL CELLOSOLVE (111-76-2)	450 ppm (2.175 mg/L)	530 mg/kg	400-500 mg/kg

Other important toxicological hazards: None reported by the manufacturer.

## 12. Ecological information

### 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

#### Aquatic Ecotoxicity

Ecotoxicity: Not expected to be harmful to aquatic organisms. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. Do not allow material to contaminate ground water system. See the following tables for the substance's ecotoxicity data.

### 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

#### Aquatic Ecotoxicity

##### Toxicity to Fish

Ingredient	96 hr. LC50 fish, mg/l	NOEC / 21 day	M Factor
BUTYL CELLOSOLVE (111-76-2)	1490 mg/L (Lepomis macrochrius)	>100 mg/L (Zebra fish)	None.

##### Toxicity to Daphnia

Ingredients	EC50 / 48h	NOEC / 21 day	M Factor
BUTYL CELLOSOLVE (111-76-2)	>835 mg/L (Daphnia magna)	100 (Daphnia magna)	None.

##### Toxicity to Algae

Ingredients	EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor
BUTYL CELLOSOLVE (111-76-2)	> 911 mg/L/96hr (Green algae)	>286 mg/L (Green algae)	None

#### Persistence and degradability:

Readily biodegradable.

#### Bioaccumulation potential:

Not expected to bioaccumulate.

Ingredients	Partition coefficient n-octanol/water (log Kow)	Bioconcentration factor (BCF)
BUTYL CELLOSOLVE (111-76-2)	0.81 at 25 °C	0.97

# Safety Data Sheet

## PAINT REMOVER

SDS Revision Date: 01/06/2022



**Mobility in soil:** No data is available on the product itself.

**Other Adverse Environmental effects:**  
No data is available on the product itself

### 13. Disposal considerations

#### 13.1. Waste treatment methods

**Handling for Disposal:** Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.

**Methods of Disposal:** Dispose in accordance with all applicable federal, state, provincial and local regulations.

**RCRA:** If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies

### 14. Transport information

	<b>DOT (Domestic Surface Transportation)</b>	<b>IMO / IMDG (Ocean Transportation)</b>	<b>ICAO/IATA</b>
<b>14.1. UN number</b>	Not Applicable	Not Regulated	Not Regulated
<b>14.2. UN proper shipping name</b>	Not Regulated	Not Regulated	Not Regulated
<b>14.3. Transport hazard class(es)</b>	<b>DOT Hazard Class:</b> Not Applicable	<b>IMDG:</b> Not Applicable <b>Sub Class:</b> Not Applicable	<b>Air Class:</b> Not Applicable
<b>14.4. Packing group</b>	Not Applicable	Not Applicable	Not Applicable

#### 14.5. Environmental hazards

**IMDG** Marine Pollutant: No

#### 14.6. Special precautions for user

No further information

Special precautions for user: Appropriate advice on safety must accompany the package. Keep away from heat and open flames. - No smoking.

Environmental hazards: This product does not meet the criteria for an environmentally hazardous mixture, according to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not available.

### 15. Regulatory information

#### US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

# Safety Data Sheet

## PAINT REMOVER

SDS Revision Date: 01/06/2022



Ingredients	TSCA Inventory	CERCLA Reportable Quantity (RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical  Toxic Chemical de minimus Concentration
BUTYL CELLOSOLVE (111-76-2)	Yes	N/Ap	N/Ap	No N/Ap

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Immediate (Acute) health hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

### US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

Ingredients	California Proposition 65		State "Right to Know" Lists					
	Listed	Type of toxicity	CA	MA	MN	NJ	PA	RI
BUTYL CELLOSOLVE (111-76-2)	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes

### Canadian Information:

Canadian Environmental Protection Act (CEPA): All ingredients are present on the DSL.  
WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

### International Information:

Components listed below are present on the following International Inventory list

Ingredients	CAS #	European EINE Cs	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	China IECSC
BUTYL CELLOSOLVE	111-76-2	203-905-0	Present	Present	(7)-97; (2)-407	KE-04134	Present	HSR001154

## 16. Other information

### Legend

ACGIH: American Conference of Governmental Industrial Hygienists  
 CA: California  
 CAS: Chemical Abstract Services  
 CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980 CFR: Code of Federal Regulations

# Safety Data Sheet

## PAINT REMOVER

SDS Revision Date: 01/06/2022



CNS: Central Nervous System  
COC: Cleveland Open Cup  
CSA: Canadian Standards Association  
DOT: Department of Transportation  
EPA: Environmental Protection Agency  
HMIS: Hazardous Materials Identification System  
HSDB: Hazardous Substances Data Bank  
IARC: International Agency for Research on Cancer  
Inh: Inhalation  
LC: Lethal Concentration  
LD: Lethal Dose  
MA: Massachusetts  
MN: Minnesota  
N/Ap: Not Applicable  
N/Av: Not Available  
NFPA: National Fire Protection Association  
NIOSH: National Institute of Occupational Safety and Health  
NJ: New Jersey  
NTP: National Toxicology Program  
OSHA: Occupational Safety and Health Administration  
PA: Pennsylvania  
PEL: Permissible exposure limit  
RCRA: Resource Conservation and Recovery Act  
RI: Rhode Island  
RTECS: Registry of Toxic Effects of Chemical Substances  
SARA: Superfund Amendments and Reauthorization Act  
STEL: Short Term Exposure Limit  
TLV: Threshold Limit Values  
TWA: Time Weighted Average  
WHMIS: Workplace Hazardous Materials Identification System

### References

1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2016
2. International Agency for Research on Cancer Monographs, searched 2016
3. Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases, 2016(Chempendium, HSDB and RTECS).
4. Material Safety Data Sheets from manufacturer.
5. US EPA Title III List of Lists - 2016 version.
6. California Proposition 65 List - 2016 version.
7. OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2016.

### Other special considerations for handling:

Provide adequate information, instruction and training for operators.

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

# Safety Data Sheet

## PAINT REMOVER

SDS Revision Date: 01/06/2022



The opinions expressed are those of qualified experts within ComStar International Inc. We believe that the information contained is current as of the date of the Safety Data Sheet. Since the use of this information and of these opinions and the conditions of the use of the product are not within the control of ComStar International Inc., it is the user's obligation to determine the conditions of safe use of the product.

End of Document