

# Safety Data Sheet

## TIRE DRESSING PROTECTANT-ALL SEASON GRADE

SDS Revision Date: 08/01/2026



### 1. Identification

**Product Name:** TIRE DRESSING PROTECTANT-All SEASON GRADE  
**Common Name:** 71-101, Blended, Tire Dressing Protectant-All Season Grade, Silicone Protectant for Rubber & Vinyl for All Season V.O.C.- 55 gallon  
**CAS Number:** Blend  
**Synonyms:** Petroleum Hydrocarbon Solvent, High Flash Point

**Company Identification:**

**Manufactured for:**  
COMSTAR INTERNATIONAL, INC.  
20-47 128th Street  
College Point, NY 11356

**For Product Information:** 1-800-328-0142

### 2. Hazard(s) identification

**2.1. Classification of the substance or mixture**

**WARNING!** CAUSES EYE IRRITATION. MAY FORM EXPLOSIVE PEROXIDES.



**Signal Word: Hazard**

DANGER

**Classes/Categories:**

Flammable liquid, Category 4.  
Skin irritant, Category 2. Serious eye irritation, Category 2A.

**SDS Number: 9072501**

**Hazard Statement(s):**

H227: Combustible liquid.  
H304: May be fatal if swallowed and enters airways.  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H336: May cause drowsiness or dizziness.

**Precaution Statement(s):**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ eye protection/ face protection.

# Safety Data Sheet

## TIRE DRESSING PROTECTANT-ALL SEASON GRADE



SDS Revision Date: 08/01/2026

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.  
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P331 Do NOT induce vomiting.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol resistant foam for extinction.  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.  
P501 Dispose of contents/ container to an approved waste disposal plant.

### Other Hazard Statement(s):

-NFPA Ratings:  
Health = 2  
Fire = 2  
Reactivity = 0

## 3.Composition/information on ingredients

Mixture of the substances listed below with nonhazardous additions.

Chemical Name	CAS Number	Percentage
Distillates (pet), hydrotreated light	64742-47-8	0-80

\*Any concentration shown as a range is to protect confidentiality or is due to batch variation.

## 4.First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.

#### Skin Contact:

Wash off immediately with plenty of water while removing all contaminated clothes and shoes. When symptoms persist or in all cases of doubt seek medical advice. Wash contaminated clothing before re-use.

# Safety Data Sheet

TIRE DRESSING PROTECTANT-ALL SEASON GRADE

SDS Revision Date: 08/01/2026



- Eye Contact:** Flush immediately with large amounts of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Gently remove contacts while flushing. Get medical attention if irritation persists.
- Ingestion:** If swallowed, call a poison control center or doctor immediately. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.
- Symptoms and Effects, both acute and delayed:** No further relevant data available.
- Recommended Actions:** Treat symptomatically. Call a doctor or poison control center for guidance.

## 5. Fire-fighting measures

- Recommended Fire Extinguishing Equipment:** COMBUSTIBLE LIQUID NFPA CLASS IIIA: Use carbon dioxide fire extinguishers. Water will be ineffective in fighting an oil fire unless used by experienced fire fighters. Do NOT use high-volume water jet.
- Possible Hazards During a Fire:** Do not allow run-off from fire fighting to enter drains or water courses. Do not use a solid water stream as it may scatter and spread fire. Cool closed containers exposed to fire with water spray. Hazardous combustion products may include unidentified organic and inorganic compounds.
- Recommendations to Firefighters:** Proper protective equipment including breathing apparatus.

## 6. Accidental release measures

- Personal Precautions:** Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Material can create slippery conditions.
- Environmental Precautions:** Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.

# Safety Data Sheet

TIRE DRESSING PROTECTANT-ALL SEASON GRADE



SDS Revision Date: 08/01/2026

## Cleanup Procedures:

Contain spillage, and then collect with noncombustible absorbent material, (e.g. sand, earth, diatomaceous earth, Vermiculite) and place in container for disposal according to local / national regulations. Keep in suitable, closed containers for disposal.

## 7. Handling and storage

### Handling Precautions:

Handle with care and avoid spillage on the floor. Do not cut, weld, drill, grind, braze, or solder container. Keep away from heat. Avoid formation of aerosol. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust. Ensure all equipment is electrically grounded before beginning transfer operations.

### Storage Requirements:

Prevent unauthorized access. No smoking. Keep container tightly closed in a dry and well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

## 8. Exposure controls and personal protection

### Exposure Limits:

-Distillates (pet), hydrotreated light AND/OR Solvent naphtha (petroleum), heavy aliph. (>90%):  
ACGIH TWA – 200mg/m<sup>3</sup> (total vapor)  
OSHA P0 TWA – 400ppm, 1600mg/m<sup>3</sup>  
OSHA Z-1 TWA – 500ppm, 2000mg/m<sup>3</sup>

### Engineering Controls:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).

### Personal Protective Equipment:

Wash hands before breaks and at the end of work. In the case of vapour formation use a respirator with an approved filter. Use safety glasses and gloves. Avoid contact with skin and clothing.

# Safety Data Sheet

TIRE DRESSING PROTECTANT-ALL SEASON GRADE



SDS Revision Date: 08/01/2026

## 9. Physical and chemical properties

<b>Color:</b>	Colorless
<b>Physical State:</b>	Liquid
<b>Odor:</b>	Mild Hydrocarbon
<b>Odor Threshold:</b>	Data not available
<b>pH:</b>	Data not available
<b>Melting Point:</b>	-45° C / -49° F
<b>Boiling Point:</b>	200° C / 392° F
<b>Boiling Range:</b>	200-300° C / 392-572° F
<b>Flash Point:</b>	80-96° C / 176-205° F
<b>Evaporation Rate:</b>	<0.1 (where Butyl Acetate = 1)
<b>Flammability:</b>	Data not available
<b>Flammability Limits:</b>	Data not available
<b>Vapor Pressure:</b>	0.02-0.06 kPa at 68 °F
<b>Vapor Density:</b>	4.5
<b>Relative Density:</b>	0.821 g/cm <sup>3</sup> at 68° F
<b>Solubilities:</b>	Insoluble in water
<b>Partition Coefficient:</b>	Data not available
<b>Auto-Ignition Temperature:</b>	232° C / 449° F
<b>Decomposition Temperature:</b>	Data not available
<b>Viscosity:</b>	0.1 mm <sup>2</sup> /sec (kinematic at 40° C)

## 10. Stability and reactivity

<b><u>Stability:</u></b>	Stable under normal conditions.
<b><u>Reactivity:</u></b>	Not reactive under normal conditions.
<b><u>Conditions to Avoid:</u></b>	Extreme temperature, sparks, open flame, and direct sunlight.
<b><u>Hazardous Reactions:</u></b>	No known hazardous reactions.
<b><u>Incompatible Materials:</u></b>	Strong oxidizers.
<b><u>Decomposition Products:</u></b>	Hazardous decomposition products are not expected to form.

# Safety Data Sheet

TIRE DRESSING PROTECTANT-ALL SEASON GRADE

SDS Revision Date: 08/01/2026



## 11. Toxicological information

### Routes of Exposure:

Skin, inhalation, and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

### Exposure Effects:

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

### Measures of Toxicity:

Acute oral toxicity:  
LD50 (Rat): > 5,000 mg/kg  
Acute inhalation toxicity:  
No data available  
Acute dermal toxicity:  
LD50 (Rabbit, male and female): > 2,000 mg/kg  
Method: Fixed dose procedure  
GLP: yes  
Assessment: The substance or mixture has no acute dermal toxicity  
Skin corrosion/irritation  
Species: Rabbit  
Exposure time: 24 h  
Method: In vivo  
Result: Irritating to skin.  
  
Serious eye damage/eye irritation  
Species: Rabbit  
Result: Irritating to eyes.  
Method: In vivo  
Respiratory or skin sensitization  
Test Type: Buehler Test  
Exposure routes: Dermal  
Species: Guinea pig  
Method: In vivo  
Result: Did not cause sensitization on laboratory animals.  
GLP: yes

# Safety Data Sheet

TIRE DRESSING PROTECTANT-ALL SEASON GRADE



SDS Revision Date: 08/01/2026

STOT- Single Exposure:

Inhalation, Central Nervous System, May cause drowsiness or dizziness. The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects

**Carcinogenic/Mutagenic  
Precautions:**

Non-carcinogenic and not expected to be mutagenic.

## 12. Ecological information

**Ecological Precautions:**

Avoid exposing to the environment.

**Ecological Effects:**

Toxicity to fish:

LL50 (Oncorhynchus mykiss (rainbow trout)): 25 mg/l

Exposure time: 96 h

Test Type: static test

Analytical monitoring: yes

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other aquatic invertebrates:

EL50 (Daphnia magna (Water flea)): 1.4 mg/l

Exposure time: 48 h

Test Type: static test

Analytical monitoring: yes

Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae:

EL50 (Pseudokirchneriella subcapitata (green algae)):

1 mg/l

End point: Growth rate

Exposure time: 72 h

Test Type: static test

Analytical monitoring: yes

Method: OECD Test Guideline 201

GLP: yes

Ecotoxicology Assessment

Acute aquatic toxicity:

Toxic to aquatic life.

Chronic aquatic toxicity:

Toxic to aquatic life with long lasting effects.

# Safety Data Sheet

TIRE DRESSING PROTECTANT-ALL SEASON GRADE

SDS Revision Date: 08/01/2026



## 13. Disposal considerations

<b><u>Disposal Methods:</u></b>	Dispose of waste material in accordance with all local, state, and federal requirements.
<b><u>Disposal Containers:</u></b>	Use properly approved container for disposal.
<b><u>Special Precautions:</u></b>	Do not flush to surface waters or drains.

## 14. Transport information

<b><u>UN Number:</u></b>	UN1268
<b><u>UN Shipping Name:</u></b>	Petroleum Distillates, n.o.s.
<b><u>Transport Hazard Class:</u></b>	3
<b><u>Packing Group:</u></b>	III
<b><u>Environmental Hazards:</u></b>	Data not available
<b><u>Bulk Transport Guidance:</u></b>	Data not available
<b><u>Special Precautions:</u></b>	The flash point for this material is greater than 100 F (38 C). Therefore, in accordance with 49 CFR 173.150(f) non-bulk containers (<450L or <119 gallon capacity) of this material may be shipped as non-regulated when transported solely by land, as long as the material is not a hazardous waste, a marine pollutant, or specifically listed as a hazardous substance.

## 15. Regulatory information

This material and all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substances Control Act.

## 16. Other information

The information contained in this Safety Data Sheet (SDS) relates only to the specific material designated. LYDEN OIL COMPANY assumes no legal responsibility of the use or reliance upon this data. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the LYDEN OIL COMPANY.